

MG 4000 SD-5/ES – Tin 12

4kVA Tin 12 Diesel Generator

When looking for robust, reliable, good quality 4kVA Tin 12 diesel generator, look no further than our MG 4000 SD-5/ES – Tin 12. Fusion models are designed to suit Tin 12 gas and water applications for butt + electro boxes – 110V CTE.

Features

- 4kVA (110V)
AC Aux Power

- Linz alternator

- Kohler/ Lombardini diesel engine (Stage 5)

- HVO (Hydrotreated Vegetable Oil) fuel approved

- Complete with trolley kit + folding handles

- Only 84kg

- Complete with electric starting system

Benefits

- Plenty of power to run small gas and water applications

- Heavy duty and proven reliability

- Electric start, power, reliability and robust strength

- Suitable to run off either diesel, HVO or a mixture of both fuels

- For nice and easy manoeuvrability and storage

- Lightweight design

- Effort-free start up



Specification

Performance

Alternator	Linz	Noise Level	LWA=95 dBa@7m=70
Single Phase Power (110V)	4kVA/ 3.2kW	Insulation Class	H
Single Phase Power (230V)	N/A	Mechanical Protection - IP	23

Engine

Make	Kohler/ Lombardini	Cooling	Air
Type	15LD350 (Stage 5)	Fuel Consumption @ 75% Load (Litres/hour)	1
Fuel	Diesel / HVO (HVO = BS EN 15940:2016 Only)	Fuel Tank Capacity (Litres)	13
Number of Cylinders	1	Average Runtime @ 75% Load (Hours)	13
Power (HP)	6.5	CO ₂ Output Per Hour @ 75% Load	2.62kg
Engine Speed (RPM)	3000	Starting System	Electric

Dimensions (Machine only)

Length: 765 mm	Width: 525 mm	Height: 590 mm
Dry Weight (No Fuel): 91 kg		Wet Weight (Fuel Full): 104 kg

Dimensions (Trolley kit with handles folded out)

Length: 1460 mm	Width: 750 mm	Height: 725 mm
Dry Weight (No Fuel): 96 kg		Wet Weight (Fuel Full): 109 kg

Socket Configuration

	1ph (110V)	
	32A	16A
MG 4000 SD-5/ES – Tin 12	1	2

For more details call **MHM TODAY**
on **0808 168 9099**

Email sales@mhmplant.com or visit us at www.mhmplant.com

