

MG 8000 SSK

Ready to Rent 8kVA Diesel Generator

When looking for a robust, reliable, good quality 8kVA diesel generator, look no further than our MG 8000 SSK.



Optional extras:



Water Cooled
Extra Super
Silent

Stage 3
Engine



Kubota
2 Year Engine
Warranty (Limited)

Features

- 8kVA (230V / 110V) AC Aux Power
- Linz alternator
- Kubota diesel engine (Stage 3)
- HVO (Hydrotreated Vegetable Oil) fuel approved
- Exclusive MHM engine protection shutdown system
- Emergency stop button
- Central lifting eye and front & side fork pockets
- Fully bunded base (110%)
- Complete with trolley kit + folding handles

Benefits

- Plenty of power to meet the demands of small generator hire
- Heavy duty and proven reliability
- World class performance and watercooled
- Suitable to run off either diesel, HVO or a mixture of both fuels
- In the case of low fuel, low oil pressure and battery charge failure
- A must on any UK site
- Flexible and safe lifting on site
- To retain all spilt fluids
- For nice and easy manoeuvrability, transport and storage



Specification

Performance

Alternator	Linz	Noise Level	LWA=89 dBa@7m=64
Single Phase Power (110V)	8kVA/ 6.4kW	Insulation Class	H
Single Phase Power (230V)	8kVA/ 6.4kW	Mechanical Protection - IP	23

Engine

Make	Kubota	Cooling	Water
Type	D722E (Stage 3)	Fuel Consumption @ 75% Load (Litres/hour)	2.4
Fuel	Diesel / HVO (HVO = BS EN 15940:2016 Only)	Fuel Tank Capacity (Litres)	40
Number of Cylinders	3	Average Runtime@ 75% Load (Hours)	16
Power (HP)	17	CO2 Output Per Hour @ 75% Load	6.29kg
Engine Speed (RPM)	3000	Starting System	Deepsea 3110 c/w two wire Auto Start/ Stop facility

Dimensions (Machine only)

Length: 1220 mm	Width: 670 mm	Height: 840 mm
Dry Weight (No Fuel): 346 kg	Wet Weight (Fuel Full): 377 kg	

Dimensions (Trolley kit with handles folded out)

Length: 1635 mm	Width: 940 mm	Height: 980 mm
Dry Weight (No Fuel): 361 kg	Wet Weight (Fuel Full): 392 kg	

Dimensions (With road-tow kit)

Length: 2650 mm	Width: 1300 mm	Height: 1200 mm
Dry Weight (No Fuel): 481 kg	Wet Weight (Fuel Full): 512 kg	

Socket Configuration	1ph (230V)		1ph (110V)	
	32A	16A	32A	16A
MG 8000 SSK	1	2	2	1
Hard wire facility	1ph (230V)		1ph (110V)	
MG 8000 SSK	✓		✓	

For more details call **MHM TODAY**
on **0808 168 9099**

Email sales@mhmplant.com or visit us at www.mhmplant.com



Designed in the UK,
built in Italy

